

IN THE CLAIMS

1. (Currently Amended) A nuclear medical diagnostic apparatus, comprising:

a radiation detector in a form of a single layer including a plurality of semiconductor cells that (1) are arranged in a matrix, (2) detect radiation separately, and (3) output signals representing an energy of the radiation separately;

a selection circuit which, in order to select, among events wherein the radiation is detected, a specific event wherein radiation derived from a radio-isotope injected into a subject is detected and a total energy of not less than two respective signals substantially simultaneously output from not less than two semiconductor cells falls in a predetermined energy window;

a position calculation circuit that calculates an incidence position based on a position selected from positions of said not less than two semiconductor cells;

a counting circuit configured to count the specific event in association with the calculated incidence position; and

a circuit configured to generate a distribution of radio-isotope in the subject on the basis of a counting result.

2. (Canceled)

3. (Currently Amended) An apparatus according to claim [[2]] 1, wherein said position calculation circuit compares respective energies of the not less than two respective signals in order to select the position.

4. (Previously Presented) An apparatus according to claim 3, wherein said position calculation circuit selects, from the positions of said not less than two semiconductor cells, the position of one semiconductor cell that outputs a signal representing a minimum energy.

5. (Currently Amended) An apparatus according to claim 3, wherein said position calculation circuit selects the position[s] of one of said not less than two semiconductor cells based on the respective energies of the not less than two respective signals.

6. (Currently Amended) An apparatus according to claim 3, wherein said position calculation circuit selects, from the positions of said not less than two semiconductor cells, a the position of one semiconductor cell that outputs a signal representing a minimum energy in a first area, and a the position of one semiconductor cell that outputs a signal representing a maximum energy in a second area.

7. (Canceled)

8. (Previously Presented) An apparatus according to claim 1, wherein said selection circuit is configured to calculate time differences between a signal output from one of said plurality of semiconductor cells and signals output from remaining cells of said plurality of semiconductor cells.

9-21. (Canceled)

22. (Previously Presented) A method for generating a distribution of a radio-isotope in a subject with a nuclear medical diagnostic apparatus including a radiation detector in a

form of a single layer, the radiation detector having a plurality of semiconductor cells arranged in a matrix, comprising:

detecting radiation derived from the radio-isotope with the plurality of semiconductor cells that output respective signals;

comparing a total energy of not less than two respective signals output from not less than two semiconductor cells with a predetermined energy window; and

calculating an incident position of the radiation based on a position of only one of the not less than two respective signals output from the not less than two semiconductor cells.